







G-9/GCG-9

UPRIGHT COOLER

G-Series Coolers

FEATURES

- Exterior Dimensions (WDH): 502 x 552 x 1616 mm
- Internal Volume: 204 L
- Dynamic LED Lighting In Door Provides Enhanced Product Illumination While Greatly Reducing Energy Consumption
- Forced Air Refrigeration System For Fast Product Temperature **Pull Down**
- High Impact Side Panel Graphics
- High Density Environmentally Friendly Insulation
- **Utilizes Climate-Friendly Natural Refrigerant**
- 4 Fully Adjustable Powder-Coated Metal Shelves
- Double-Paned, Low "E", Self-Closing Glass Door
- **LED Interior Lighting**
- Durable Pre-Painted Steel Cabinet and Heavy Duty Inner Liner
- Adjustable Temperature Control
- 9' Heavy Duty Power Cord

CERTIFICATIONS

220v

- LOA (R134a, South Africa)
- (E
- ROHS
- EMC
- SAA, MEPS Compliant (R134a, Australia)
- C-Tick (R134a, Australia)
- CB Scheme









G-9/GCG-9

UPRIGHT COOLER

G-Series Coolers





SHIPPING SPECS

TECH SPECS

Refrigerant

Amps

Volts/Hz

Compressor HP

Gross Weight	85 kg
Net Weight	72 kg
Carton Dims (WDH)	
Units per Pallet	
Shipping Options:	
Pallet Loaded	20′ ~ 44
	40′HQ ∼88

R290

3.2

100V/50-60Hz

1/4

R290

2.7

220-240V/50Hz

1/5

DIMENSIONS

Exterior (WDH): 505 x 552 x 1616 mm

Interior (WDH): 413 x 400 x 1175 mm

Shelf (WD): 387x 330 mm

Internal Volume: 204 L


PACKOUT CAPACITIES

		Facings		Deep	Total Capacity	Total Rows
355ml Can	6 Shelves + Base	6	x	5	= 210*	7
	Тор	6	х	2		
500ml Can	4 Shelves + Base	6	Х	5	= 162*	6
\overline{A}						
	3 Shelves	5	Х	4	= 85**	4
591ml PET	Base	5	Х	5		

^{*}Additional shelves, beyond what is supplied with the cooler, may be required to achieve this maximum pack-out.

EXTERIOR DIMENSIONS





INTERIOR DIMENSIONS

